




FRAMELESS GLASS WALLS

No Visual Barriers!

Hufcor frameless glasswalls serve as the perfect solution for transparent barrier to close up shop fronts, restaurants, delis or ATM areas while maintaining a full view of the entire outlets.


INDIVIDUAL OMNI DIRECTIONAL PANELS

Individual Panels are top supported by two (2) carriers that operate in the track system allowing panels to move and turn effortlessly through 90 degree intersections engineered for heavy glass panels. The versatility of stack arrangements includes Perpendicular Stack, Parallel Stack, Remote or Custom Stack.




HINGED PAIRS / CENTER STACKING PANELS

Panels are hinged in pairs and are top-supported by one (1) carrier in each panel. The Center Stack arrangement provides panel storage at one or both ends of the walls installed position.



CONTINUOUSLY HINGED CENTER STACKING TRAINS – MANUAL & AUTOMATIC

Continuously Hinged Panels form a panel train allowing for easy set-up. The stacking arrangement can be at one end or bi-parting. The final closure panel can be a flipper or might just use a pivot panel at stack end. Partition operation can be manual or motorized (fully automatic).





PANEL CONSTRUCTION

Series 3630 panels are nominally 40 mm thick and up to 1100 mm in width. Panel faces are of 12 mm fully tempered glass. The glass is mechanically attached to top and bottom rails and does not rely on friction and adhesives.

Weight of the panels is approximately 36.12 Kg per sq. m for 12 mm glass.

The system is manually operated. The panels are moved from the storage area, positioned in the opening, and floor bolts set. The final closure can be secured by the following options:

1. Flipper Panel
2. Pivot panel with handle
3. Overlapping the opening
4. Pocket door



FINISHES

The horizontal rails and track finish are clear anodized aluminium, however custom anodizing - bronze or champagne is available on request. Frames can also be powder-coated to desired RAL color. Specialty or Art glass can also be integrated with the system as an option.



WARRANTY

Track, carriers, and horizontal rails are guaranteed for one year against defects in material and workmanship. The glass is not included in this warranty.



TECHNICAL DETAILS

Overhead Track and Carrier system:

Made of extruded Aluminium Alloy the track has been life cycle tested for about 10 yrs of use. Zero maintenance & smooth operation even when site conditions require segmented tracks. Top and bottom sweep seals ensure dirt free interiors.

