


Flexible space management for optimal space utilization, effective sight and sound separation



*Contact Gibca for other available options

Individual Panels (Omni - Directional)

Individual, single, manually- operated panels offer maximum room flexibility. The track system enables panels to be set at angles and at alternate locations. Curves and self-storing systems are available.

Recommended for: religious facilities, school multi-user areas, hotel ballrooms and convention centers.



Experience Hufcor 7000 Classic Series. Experience Value. **Experience Convenience.**

	Model	Acoustic Rating	Hanging Weight
DESIGN		STC	kg/sq.m.
FULL-PERIMETER ALUMINUM FRAME	7610	43	38.1
DEEP INTERLOCKING VERTICAL SEALS	7630	47	39.1
RETRACTABLE TOP & BOTTOM SEALS	7640	49	41.6
TYPE 36 OMNI-DIRECTIONAL TO 455 kg*	7650	51	41.6
* Also available in Type 57 omni directional up to 680kgs.	7660	53	53.2

Panels are nominally 100mm thick and frames are of anodized aluminium alloy 6063-T6 formed, fully captures and protect the edges of the face material.

WAX

FINISHES

We offers a standard range of vinyl which includes an array of standard patterns and colors. Other colors, patterns, carpet, fabric, high pressure laminate, wood veneers, and other design features may be added for an up-charge. We also assists interior decorators applying custom-in-field finish on our panels.

POCKET DOORS

The finishing touch to your installation, pocket doors cover the opening of the partition storage area. The pocket doors may be factory finished to match the partitions or field finished to match the perimeter walls.

ADA COMPLIANT PASS DOOR

Available in single or double doors. Hufcor pass doors comply with ADA requirements and are of the same construction and finish as the panels. No threshold or foot bolt stabilizers are required.

Exit signs Automatic door closer Panic Hardware

Locks Frame and prep for window Peep viewer

SIZES

Max. Height: 10,000 mm Partition Width: Unlimited

Pass Door Options: Single or Double









VERTICAL SECTION OF 7660 SERIES



LAYER OF 12mm GYPSUM BOARD TH SIDES (BY OTHERS)

ROCKWOOL INFILL (45 kg/m³) (BY OTHERS) 160X75X8mm FIXING PLATE

CEILING LEVEL -CARRIER TRACK TYPE 36

ROCKWOOL INFILL (45 kg/m³)









