H9

RELOCATABLE PARTITION WITH COVER-TRIMS

Relocatable partition with cover-trims provides enhanced flexibilty, sound insulation, adaptability and relocatability to suit any layout requirement.

96 mm THICK PARTITIONS

ENHANCED SOUND INSULATION

HEIGHT UP TO 6000 mm



DESIGN

■ TECHNICAL FEATURES

■ FINISHES

■ SOUND INSULATION





PARTITIONS WITH COVER-TRIMS





- 2 Cover-trims
- 3 MDF/Chipboard/Gypsum board panels
- 4 Single or double glazing
- 5 Door

3

DESIGN

Aluminium framed partition with cover-trims; brushed finish or RAL color powder coated. 2 types of assembly possible: with the OPS self-centering system of spring and excenter and/or angle bracket.

FINISHES

Panel Finishes:

2 plasterboard / melamine faced MDF / chipboard panels (12 mm)

Rockwool infill in between the panels for acoustic insulation.

Single or double glazing: 6 - 8 mm

Possible integration of Venetian blinds in double glazing.

DOORS

Aluminium doorframe:

- round or square doorcase,
- acoustic seal at the periphery.

Solid laminated doors - 40 mm thick.

Glass doors.

Aluminium framed doors with choice of glass / MDF infill panel.

Also available: Other dimensions / solid doors with overpanel, sliding doors with "Easy type" integrated rail or additional rail applied to the partition.

PANEL FINISHES

Melamine faced, laminated, vinyl covering or lacquered steel sheet. (Other finishes possible upon request).

CERTIFICATIONS

Sound insulation: from 42 to 50 dB RW **CERFF** Certification



TECHNICAL FEATURES

96 mm thickness

Standard modulation width: 1200 mm (other modulation upon request)

Standard height: Up to 6000 mm.

Correction of uneven levels or distorted bases up to ± 12.5 mm with a telescopic element. Angles: 90° angle (curved or square shape); Variable angle to suit any layout requirement.

Finishes supported by aluminium cover-trims vertically and horizontally clipped.









GIBCA FURNITURE INDUSTRY CO. LTD. (LLC)

P. O. Box 20923, AJMAN - UAE

Tel: +971-6-7436888, Fax: +971-6-7436903

e-mail: info@gfiuae.com website: www.gfiuae.com

